


**ARMY RESEARCH LABORATORY**



# **Verification and Validation of the Night Vision Goggle Tactical Decision Aid**

**by John R. Elrick  
Battlefield Environment Directorate**

ARL-MR-166

May 1995



19950711 017

DTIC QUALITY INSPECTED 5

## **NOTICES**

### **Disclaimers**

The findings in this report are not to be construed as an official Department of the Army position, unless so designated by other authorized documents.

The citation of trade names and names of manufacturers in this report is not to be construed as official Government indorsement or approval of commercial products or services referenced herein.

### **Destruction Notice**

When this document is no longer needed, destroy it by any method that will prevent disclosure of its contents or reconstruction of the document.

# REPORT DOCUMENTATION PAGE

Form Approved  
OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

1. AGENCY USE ONLY (Leave blank)		2. REPORT DATE May 1995		3. REPORT TYPE AND DATES COVERED Final	
4. TITLE AND SUBTITLE Verification and Validation of the Night Vision Goggle Tactical Decision Aid				5. FUNDING NUMBERS	
6. AUTHOR(S) John R. Elrick					
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) U.S. Army Research Laboratory Battlefield Environment Directorate Attn: AMSRL-BE-W				8. PERFORMING ORGANIZATION REPORT NUMBER ARL-MR-166	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) U.S. Army Research Laboratory 2800 Powder Mill Road Adlephi, MD 20783				10. SPONSORING/MONITORING AGENCY REPORT NUMBER ARL-MR-166	
11. SUPPLEMENTARY NOTES					
12a. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution is unlimited.				12b. DISTRIBUTION CODE A	
13. ABSTRACT (Maximum 200 words)  The Night Vision Goggle (NVG) Tactical Decision Aid (TDA) was developed to support Army operations in situations requiring accurate predictions of light levels. Minimum thresholds of illumination are used by the Army to plan and execute missions during periods of darkness or near darkness. The NVG TDA is part of a suite of decision aids that will become part of the fielded Integrated Meteorological System (IMETS). The IMETS is a system designed to be operated by Air Force Staff Weather Officers supporting Army tactical operations in peacetime and in times of conflict. The verification and validation (V & V) effort discussed in this report is part of the Battlefield Environment Directorate configuration management plan to field physically correct and user-friendly software to Army units over the entire conflict spectrum. The V & V described is thorough and shows that the NVG TDA is physically correct and applicable for accreditation before use.					
14. SUBJECT TERMS low-light, night vision, IMETS				15. NUMBER OF PAGES 42	
				16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT Unclassified	18. SECURITY CLASSIFICATION OF THIS PAGE Unclassified	19. SECURITY CLASSIFICATION OF ABSTRACT Unclassified	20. LIMITATION OF ABSTRACT SAR		

## Contents

<b>1. Introduction</b> .....	3
<b>2. Technical Documentation Review</b> .....	7
<b>3. Software Testing</b> .....	13
3.1 Notes Taken 1 Nov 93 .....	13
3.2 Notes Taken 4 Nov 93 .....	14
3.3 Notes Taken 9 Nov 93 .....	15
3.4 Notes Taken 12 Nov 93 .....	16
3.5 Notes Taken 15 Nov 93 .....	18
3.6 Notes Taken 16 Nov 93 .....	18
3.7 Notes Taken 18 Nov 93 .....	18
<b>4. Conclusions and Recommendations</b> .....	21
<b>References</b> .....	23
<b>Acronyms and Abbreviations</b> .....	25
<b>Bibliography</b> .....	27
<b>Distribution</b> .....	29

Accession For	
ETIS GRA&I	<input checked="" type="checkbox"/>
DTIC TAB	<input type="checkbox"/>
Unannounced	<input type="checkbox"/>
Justification	
By	
Distribution/	
Availability Codes	
Disc	Avail and/or Special
A-1	

# 1. Introduction

The Night Vision Goggle (NVG) tactical decision aid (TDA) is a computer software application used to determine the suitability of NVG use based on existing or forecast meteorological conditions in a specific area of interest. It provides solar and lunar illumination values and positions based on computer calculated ephemeris data. The TDA considers the general effects of clouds and precipitation on illumination levels, based on typical surface weather observations of prevailing meteorological conditions.

The NVG TDA is part of a suite of decision aids delivered to the Program Executive Office, Command and Control Systems (PEOCCS), Project Director (PD), Integrated Meteorological System (IMETS) as part of a fielded IMETS software applications package. Before this formal release, the NVG TDA was used under the guidance of Battlefield Environment Directorate (BED) scientists to support U.S. Army field training and command post exercises at various locations in the United States and Europe. This TDA was included in the Initial Operational Test and Evaluation of the Block I IMETS conducted at Fort Hood, TX during the fall of 1993.

Although the NVG TDA went through acceptance testing before the release to PEOCCS PD IMETS, formal independent verification and validation (V & V) efforts were never accomplished. The V & V described here is a result of BED's efforts to include V & V as part of future software releases to U.S. Army weather support personnel. This process is part of the BED configuration management program to ensure that accurate, user-friendly applications are fielded.

The NVG V & V discussed here, ideally, would have started at the beginning of the software development cycle and continued throughout the life-cycle of the NVG TDA until its final fielding accreditation. This effort was initiated at BED after the release of the software, and certain V & V procedures had to be omitted because of the late start. The accurate identification of software problems is an integral part of providing the end-user with a physically and theoretically sound product.

The following definitions from Army Regulation 5-11, *Army Model and Simulation Management Program* [1] are provided for completeness (M & S in these definitions refers to model and simulation):

a. Verification

(1) Verification is the process of determining that M & S accurately represent the developer's conceptual description and specifications. Verification evaluates the extent to which the M & S has been developed using sound and established engineering techniques. The verification process involves identifying and examining the stated and pertinent unstated assumptions in the M & S, examining interfaces with input databases, ensuring that source code accurately performs all intended and required calculations, reviewing output records, performing structured walk-through techniques to determine if M & S logic correctly performs intended functions, and performing M & S sensitivity analyses. Unexpected sensitivity (or lack of sensitivity) to key inputs may highlight a need to review the M & S algorithm for omissions or errors.

(2) Verification also includes appropriate data certification and M & S documentation (e.g., programmer's manual, user's guide, and analyst's manuals).

(3) Verification should normally be performed by an independent V & V (IV & V) agent but remains the responsibility of the M & S proponent to ensure accomplishment.

b. Validation

Validation is the process of determining the extent to which M & S accurately represent the real-world from the perspective of the intended use of the M & S. The validation process ranges from single modules to the entire system. Ultimately,

the purpose is to validate the entire system of M & S data, and operator-analysts who will execute the M & S. Validation methods will incorporate documentation of procedures and results of any validation effort.

The types of validation appropriate for the NVG TDA are (1) face validation, which determines whether an M & S, based on performance, seems reasonable to people who are knowledgeable about the system being modeled; and (2) peer review, which involves critical and detailed analyses of the internal representativeness of the M & S and outputs by personnel who are experts in the functional areas represented in the M & S. This determination is based on the selected examples of validation given in the document. The following sections will focus on the NVG TDA V & V starting with a review of technical documents used in the development of the NVG TDA and other documentation primarily used to corroborate methods or values presented in the TDA. The investigator's comments are included where deemed necessary.

## 2. Technical Documentation Review

A comprehensive review of the technical documents used to develop the NVG TDA and a review of technical materials related to the software release of the NVG TDA to PD IMETS were made. The review was necessary for the validation of the theoretical concepts incorporated into the computer model. The summary is presented in this section on a document-by-document basis with cross-references where necessary for comparison of values and techniques used. The validation described is conceptual, as described by Dale K. Pace in his article "Modeling and Simulation," [2] because of the maturity level of the computer application model and the relative timeliness of this V & V effort. The V & V started late in the research and development cycle because of the delayed adoption of accepted configuration management practices by BED. In theory, the V & V should have started with the initial software development and continued through the IMETS release and beyond as new improvements to the computer model are made. The first document reviewed is the basis for the illumination calculations in the NVG application prepared by the National Defence Research Organization TNO in the Netherlands. [3] AFGL-TR-82-0039, *Solar Radiative Flux Calculations from Standard Surface Meteorological Observations*, [4] is also discussed in some detail, because it is the basis for the cloud cover information applied here. Supporting documents are reviewed next. The NVG TDA user's guide is reviewed for accuracy and applicability for operational use as seen by the evaluator.

The technical basis for the NVG TDA computer application was taken from *The Computer Program ILLUM: Calculation of the Positions of Sun and Moon and the Natural Illumination*, PHL 1982-13 by Ir. A.C. van Bochove from the Physics Laboratory at the National Defence Research Organization TNO. [3] The computer program described in this report was used for solar and lunar ephemeris calculations and for the associated illumination values. This reference also provides a reasonable constant value for natural illumination in which there is little or no contribution to light levels from the sun or moon. The report contains a full description of the FORTRAN computer code used.



The NVG program calculates illumination levels from user-supplied geographical latitude and longitude of an earth-based observer and on the local mean solar time. The calculations are reported to be within 1 min of arc for a specified valid interval. Illumination levels are calculated for the sun and moon based on a horizontal plane (flat earth) for clear skies. The computer code consists of two parts: (1) astronomical, which calculates solar and lunar azimuth and altitude and lunar phase; and (2) illumination, which calculates illumination levels and the distance of the sun and moon from the earth. Not surprisingly, the program results are not reliable during eclipses; however, the computer code is structured to warn of these occurrences. The altitude dependence of the illumination and the effect of the lunar phase are taken from accepted empirical data published in the literature.

As mentioned earlier, a constant value for natural illumination is used. For conditions in which the sun and moon are well below the observer's horizon, a value of  $1.1 \times 10^{-3}$  lx (lumens (lm)  $\text{m}^{-2}$ ) is used, which is consistent with values found in the RCA *Electro-Optics Handbook* [5] of  $1.0 \times 10^{-3}$  lx. Values for maximum lunar illumination (full moon) were 0.267 lx from both references.

Another primary document for the NVG TDA was AFGL-TR-82-0039, *Solar Radiance Flux Calculations from Standard Meteorological Observations*, [4] by Ralph Shapiro of Systems and Applied Sciences Corporation under contract to the Air Force Geophysics Laboratory (now Phillips Laboratory). The results of Shapiro's work and resulting computer models were used to include the effects of cloud cover on the amount of illumination reaching the ground. In its most complex form, this model calculates the solar radiation incident at or near the earth's surface through n-layers of a model atmosphere through a system of  $2n + 2$  linear equations. These equations are a closed set of equations that account for the physical processes of reflection, transmission, and absorption of the electromagnetic radiation along its path.

To be consistent with the standard methodology for reporting cloud cover, the n-layers were taken to be three discrete cloud layers representing low, middle, and high clouds. The effects of the surface of the earth (albedo) were also considered in a cursory fashion. Specific coefficients, primarily dependent on

the cloud amount and thickness, were developed. After reflection, transmission, and absorption coefficients are determined, based on direct measurements of radiation reaching the ground and simultaneous cloud type and amount observations, the model offers the capability of determining the mean transmission and reflection characteristics of any individual cloud type. The model described here was tested against independent data and found to be accurate. The calculations used in this work were derived from scattering theory and Monte Carlo simulations.

Nine cloud types were chosen to represent the cloud types commonly observed. The Synoptic Cloud Code recognizes other cloud types, but their occurrence is rare and they are seldom observed. The lowest cloud types considered are cumulus, stratocumulus, and stratus in which stratocumulus and stratus are combined. Middle clouds are made up of altostratus and altocumulus. Thin and thick cirrus clouds represent the high cloudiness and are combined but differentiated by their thickness (thin and thick). The case in which precipitation is occurring is the least reliable solar flux calculation used in the model because of the infrequent occurrences leading to a small number of case studies and the several different cloud types present during precipitation events. During precipitation, ground-based observers, typically, report the clouds accurately only up to the first overcast layer unless the observer has detailed supplemental information from meteorological satellites or from another source such as balloon soundings or aircraft reports. Because of this, thick clouds are assumed at all three levels (low, middle, and high) when precipitation is occurring.

In this application, simple radiative transfer processes are considered. Processes such as aerosol and molecular scattering and absorption and ozone and water vapor absorption are treated in the most rudimentary fashion. "Since the largest effect of insolation is due to clouds and since we are approximating the atmosphere with only three layers, a more sophisticated treatment of the clear layers was deemed unwarranted." [4]

The respective transmission, reflection, and absorption for each of the three cloud layers in Shapiro's treatment were handled accurately and correctly according to atmospheric physical processes. Even though this treatment is

greatly simplified by considering a simple three-layer atmosphere, the dynamics of the radiation reaching the earth's surface is very complicated. Shapiro rigorously and completely handles this physical process. [4]

The evaluator did extensive analyses of the cosine dependence on solar radiation with altitude. The analyses showed that the variation in the insolation was largely independent of the angle of incidence at altitudes below 10,000 ft with the variation in the fourth decimal place at angles less than 90°. Because most Army operations involving NVGs occur at low altitudes, the incidence angle of the radiation with altitude was considered insignificant, especially, in view of the other simplifying assumptions already made.

Finally, the *Technology Exploitation Weather TestBed (TEWTB) User's Guide and Technical Reference for the Block I Integrated Meteorological System (IMETS)*, PSL-92/60 [6] was reviewed for content and consistency. This document was prepared for and intended to be used by individuals unfamiliar with the IMETS but who possessed some basic computer operations skills. Some inconsistencies were noted in this review; however, it is a very useful document.

The user's guide employs the terminology night vision devices interchangeably with NVG. This is misleading because the Army has other equipment intended for use under low-light level conditions, which are not NVGs. Examples of these are the starlight scope used for night operations with the M-16 rifle and the tank gunner's sight used in night armor operations. The NVG application is geared more toward aviation uses for nighttime flying at low altitudes, not other operations.

References are made to conditions as being GO or NO-GO in some cases and as being Favorable/Marginal/Unfavorable in others. The terms GO/NO-GO should be avoided in any kind of a decision aid because of their restrictive nature and seeming inflexibility to adapt to changing situations. These are decision aids for use by operational decision makers, and they should not appear to be directive in nature.

Computer jargon is used in several places. This is probably acceptable for the intended audience for this early release. A careful review of future user's guides intended for operational use by Air Force Staff Weather Officers will be necessary to avoid potential confusion. For example, alphanumeric display could be replaced with something like tabular display for clarity.

The user's guide is not internally consistent in places. In some places, three cloud layers are mentioned, and in other places, four are mentioned. The model actually has four layers with the surface of the earth being a distinct surface along with the three cloud layers previously mentioned. There should be a specific input for atmospheric obscurations such as fog, smoke, haze, etc. that apply to partial (-X) and total (X) obscurations. The obscuration entries should be part of the forecaster input. The input form (screen) should have examples of expected input. For example, the month could be represented be 1-12 or Jan-Dec.

The reference should contain definitions of the unfamiliar terminology used. Some people operating the IMETS will not remember the difference between nautical and civil twilight. Inclusion of these definitions will make the document a valuable reference for the operator. The guide is complete and fairly accurate for its stage of development and intended use in the research and development cycle.

### **3. Software Testing**

During testing, the NVG TDA computer software was exercised approximately 11.5 h in seven separate sessions. The testing was done on the ACCS4 system located in building 1646 room 18. The most current version of the Block I IMETS baseline software resides on the ACCS4 system. The purpose of the testing was to evaluate the user friendliness of the NVG software suite from an operator's point of view and to determine obvious inconsistencies in the computer application. Other errors were not discovered in the testing because of the evaluator's inability to determine and analyze every possible scenario. The following is a list of the notes taken during the software testing phase of this validation effort:

#### **3.1 Notes Taken 1 Nov 93**

Hardware Platform: ACCS4

Time on System: Approximately 2 h

Went through the example scenario in the user's guide

NVG input screen has a typo, "Time difference between loca and GMT (hrs);" loca should be local. A discrepancy report form was filed.

The user must make sure that an item is highlighted before it is accepted by the program. Simply changing the entry is not enough; this is not a big deal but could give a person without computer operation experience a fit. Training on the use of the x-windows system should clear this up.

It is not obvious that latitude and longitude are in the form deg, min, sec from looking at the values. Maybe the units should be included here. This is particularly true when there is only one digit for minutes and seconds.

(6) in the user's guide example "PLOT OF GO/NO-GO TIMES" is not a menu option in the NVG application, but "PLOT OF FAVORABLE/UNFAVORABLE" is.

Daily event times should have four digits. Morning times should have the leading zero, if needed. For example, 730 should be 0730. This would conform to the military (24-h clock) way of telling and representing time.

Suggestion: Moonrise and moonset are not explicitly defined. It might be a good idea to just have a table with the nautical and civil twilights as well as moonrise/moonset. Sunrise and sunset could also be included because they are often used by Army operations personnel.

### **3.2 Notes Taken 4 Nov 93**

Hardware Platform: ACCS4

Time on System: Approximately 2 1/2 h

This is the disclaimer statement that precedes the application:

UNVERIFIED, DEVELOPMENTAL SOFTWARE FOR TRAINING AND EVALUATION ONLY Operational use requires near real-time meteorological data from surface, upper air, and satellite sensors and weather forecasts for the local area. Optimally, the host computer will automatically ingest the meteorological data and process weather decision aids. Before operational use this software must be approved according to DoD Directive 5000.3 and procedures given in DoD-STDS 2167A and 2168.

See discrepancy report forms for errors detected.

The form that is displayed for the daily event times should be made so that the dates can be read after the slide bar is used to reveal the data that would not fit on the screen. The headers (BMNT, EENT, etc.) should also be visible when the data slides down for the user to view it. It is real hard to tell what data is in the columns and rows unless they are identified in some way.

Data that were requested for 31 Nov 93 (no such date) were identical to the data for 1 Dec 93. This is a good finding in that when a bogus date is chosen, all other data are not shifted one day.

### 3.3 Notes Taken 9 Nov 93

Hardware Platform: ACCS4

Time on System: 2 1/2 h

The ACCS4 computer had to be rebooted in order for the system to work. It is not obvious that the system was down when the application was entered.

PLOT OF FAVORABLE/UNFAVORABLE Worked well for 1 day. The screen depicts a red-amber-green display which is easy to read and understand.

PLOT OF ILLUMINATION LEVELS This is a line graph. The yellow band is hard to distinguish as yellow, if it is small. There should be some indication of what is favorable and unfavorable on the chart.

ILLUMINATION CALCULATION This seemed to work fine but the time reference either Z or L should be on the input value box/screen. It will default to 0000Z if nothing is input.

The plot of favorable/unfavorable comes up behind other screens when it should come up in front automatically.

When changed, the NVG input screen should come up with the new values that were input rather than what they were when the program was entered. The site ID, weather, cloudiness, and GMT time difference come up to the original values when the NVG program is exited.

The Light Level Planning Calendar (LLPC) is hard to follow and probably should be color coded or something. The legend goes away when the slide bar is used.

Whenever a ground or surface type is specified, the value of its corresponding albedo should be available to the operator. Maybe it would be helpful if the operator could change the albedo based on local conditions and/or knowledge of the surface.

### 3.4 Notes Taken 12 Nov 93

Hardware Platform: ACCS4

Time on System: 1/2 h

The ACCS4 system booted normally. Twilight values from the NVG program were compared to hard copy printout values from the Nautical Almanac Office at the U.S. Naval Observatory in Washington, DC.

Table 1 lists the comparisons of the data from the NVG Application and the table from the White Sands Missile Range weather forecasting facility (C-Station) (the values are the deviation of the NVG program to the Nautical Almanac values. All non-zero values are positive unless noted otherwise).

These data show some differences but they are minor and could be attributed to differences in calculation methodology or some sort of a computer routine that rounds values off differently. These values are certainly within reasonable limits based on the accuracy needed for Army operations. There is good internal consistency between these two independent sources of data. The same analysis was conducted for the other eleven months of the year and the largest absolute difference between the two methodologies was 5 min. The stated requirement for accuracy was that the computer-generated data be within 5 min on either side of the actual event. The Nautical Almanac Office data are widely used throughout the world by U.S. Government agencies. Based on this, the NVG application data are good and very useful.

The values for latitude and longitude that were input to the NVG application were the same as those provided for C-Station tables to the Naval Observatory. These values were:

- a. Latitude = 32° 23' North
- b. Longitude = 106° 29' West



**Table 1. List of the comparisons of the data from the NVG application and the table from C station**

January 1993				
Date	BMNT <sup>a</sup>	BMCT <sup>b</sup>	EECT <sup>c</sup>	EENT <sup>d</sup>
1	2	2	-3	-2
2	2	3	-3	-3
3	2	3	-3	-3
4	1	3	-3	-3
5	2	3	-3	-3
6	2	2	-4	-3
7	2	2	-3	-4
8	2	2	-3	-4
9	2	1	-3	-3
10	2	1	-4	-3
11	2	2	-4	-4
12	2	1	-3	-4
13	2	1	-3	-4
14	2	1	-3	-3
15	2	1	-4	-4
16	2	1	-4	-4
17	1	1	-4	-4
18	1	0	-4	-4
19	2	1	-3	-3
20	2	1	-3	-4
21	1	0	-3	-4
22	1	1	-4	-4
23	2	1	-4	-4
24	1	0	-4	-4
25	1	1	-4	-3
26	1	0	-4	-4
27	1	1	-4	-4
28	2	0	-3	-4
29	1	1	-3	-4
30	1	0	-3	-4
31	1	1	-4	-5

<sup>a</sup>BMNT = beginning morning nautical twilight (center of the solar disk 12° below the horizon in the morning)

<sup>b</sup>BMCT = beginning morning civil twilight (center of the solar disk 6° below the horizon in the morning)

<sup>c</sup>EECT = ending evening civil twilight (center of the solar disk 6° below the horizon in the evening)

<sup>d</sup>EENT = ending evening nautical twilight (center of the solar disk 12° below the horizon in the evening)

NOTE: The definitions for BMNT, BMCT, EECT, and EENT were taken from the *Glossary of Meteorology*. [7]

### **3.5 Notes Taken 15 Nov 93**

Hardware Platform: ACCS4

Time on System: 1 h

The ACCS4 would not enable me to get to the White Sands Missile Range map display and the NVG application would not execute. I tried three or four different times. There was no outward indication that anything was wrong with the application except that it would not come on as expected.

### **3.6 Notes Taken 16 Nov 93**

Hardware Platform: ACCS4

Time on System: 1 h

On 16 Nov, the system behaved itself and worked normally. I made copies of the solar ephemeris from the ACCS for comparison with the C-Station data. The results are discussed in the 12 Nov notes.

### **3.7 Notes Taken 18 Nov 93**

Hardware Platform: ACCS4

Time on System: 2 h

The following was noted:

- a. On the LLPC, the user cannot maximize the application window screen but the capability to do it is still active. The system has a protection mechanism built in that requires you to log back in. Since this maximize capability really doesn't do anything, it probably should be disabled to avoid confusion.
- b. The same process described above also happens with the map in that the user must log back in. The map does come up on the whole screen after log-in. This is confusing to the operator.

c. When the LLPC is displayed, it is really only partially represented on the screen and the slide bars must be used to see other parts of the table. When the user tries to print the screen, all that is printed is the information on the computer screen. In order to get a printout of the table, the operator must make multiple copies of screens. The window will not expand to show the complete table.

d. The table on the LLPC is hard to understand. Possibly it could be colored for favorable, marginal, and unfavorable or contoured with only a few large letters/symbols in each area. This would make the table interpretation easier for the operator or anyone who was receiving a briefing from a hard-copy print or directly from the computer screen.

Errors that were noted in this testing were fully documented on established discrepancy report forms and reported to the responsible parties in accordance with established BED configuration management procedures.

## **4. Conclusions and Recommendations**

The NVG TDA is complete and accurate based on its stage of development in the IMETS scheme. It is based on sound physical principles and is usable and trustworthy for limited operational considerations. Before the software and hardware can be fielded, they must be made user-friendly. Any errors noted in this memorandum report and subsequent V & V efforts must be corrected. The NVG TDA must continue to be fully tested and independently evaluated in each baseline phase of its development before it is fielded as part of an operational IMETS for Army weather support. As in the past, periodic testing of changes and upgrades to the computer code by the software developers are necessary to verify the correctness of the computer code and its interaction with its associated computer hardware platform. Independent V & V must be thoroughly conducted before future IMETS releases.

## References

1. Headquarters Department of the Army, *Army Model and Simulation Management Program*, Army Regulation 5-11, Issued by Washington, DC, 10 June 1992.
2. Pace, D. K., "Modeling and Simulation," *Phalanx, The Bulletin of Military Operations Research*, 26, 3, ISSN 0195-1920, The Johns Hopkins University Applied Physics Laboratory, p 27-29, 1993.
3. van Bochove, Ir. A.C., *The Computer Program ILLUM: Calculation of the Positions of Sun and Moon and the Natural Illumination*, PHL 1982-13, Physics Laboratory TNO, National Defence Research Organization TNO, The Netherlands, 1982.
4. Shapiro, R., *Solar Radiative Flux Calculations from Standard Surface Meteorological Observations*, AFGL-TR-82-0039, Scientific Report No. 1, Systems and Applied Sciences Corporation, Document published under contract F19628-81-C-0042 for the Air Force Geophysics Laboratory, Hanscom AFB, MA, 1982.
5. *Electro-Optics Handbook*, Technical Series EOH-11, RCA, Solid State Division, Electro-Optics Devices, Lancaster, PA, Reprinted, 1978.
6. Physical Science Laboratory, *Technology Exploitation Weather TestBed (TEWTB) User's Guide and Technical Reference for the Block I Integrated Meteorological System (IMETS)*, PSL-92/60, Document published under contract DAAD07-91-C-0139 (WAO 92-3.24-2), Las Cruces, NM, November 1992.
7. Huschke, R. E., Ed., *Glossary of Meteorology*, American Meteorological Society, 1959.

## Acronyms and Abbreviations

BED	Battlefield Environment Directorate
C-Station	White Sands Missile Range weather forecasting facility
IMETS	Integrated Meteorological System
LLPC	Light Level Planning Calendar
NVG	Night Vision Goggle
PD	Project Director
PEOCCS	Program Executive Office, Command and Control Systems
TDA	tactical decision aid
V & V	verification and validation

## Bibliography

Harris, J. E., "A Technology Exploitation Weather TestBed for Army Applications," In *Proceedings of the Eighth International Conference on Interactive Information and Processing Systems for Meteorology, Oceanography, and Hydrology*, presented by J. R. Elrick, Atlanta, GA, p 5-9, January 5-10, 1992.

Nautical Almanac Office, *Lunar Ephemeris Tables for White Sands Missile Range, NM for 1993*, U.S. Naval Observatory, Washington, DC.

Physical Science Laboratory, PSL-93/57, under contract DAAD07-91-C-0139 (WAO 93-3.24-2), *Verification, Validation, and Assessment for the Technology Exploitation Weather TestBed (TEWTB)*, Las Cruces, NM, August 1993.

## Distribution

	Copies
ARMY CHEMICAL SCHOOL ATZN CM CC ATTN MR BARNES FT MCCLELLAN AL 36205-5020	1
NASA MARSHAL SPACE FLT CTR ATMOSPHERIC SCIENCES DIV E501 ATTN DR FICHTL HUNTSVILLE AL 35802	1
NASA SPACE FLT CTR ATMOSPHERIC SCIENCES DIV CODE ED 41 1 HUNTSVILLE AL 35812	1
ARMY STRAT DEFNS CMND CSSD SL L ATTN DR LILLY PO BOX 1500 HUNTSVILLE AL 35807-3801	1
ARMY MISSILE CMND AMSMI RD AC AD ATTN DR PETERSON REDSTONE ARSENAL AL 35898-5242	1
ARMY MISSILE CMND AMSMI RD AS SS ATTN MR H F ANDERSON REDSTONE ARSENAL AL 35898-5253	1
ARMY MISSILE CMND AMSMI RD AS SS ATTN MR B WILLIAMS REDSTONE ARSENAL AL 35898-5253	1



ARMY MISSILE CMND AMSMI RD DE SE ATTN MR GORDON LILL JR REDSTONE ARSENAL AL 35898-5245	1
ARMY MISSILE CMND REDSTONE SCI INFO CTR AMSMI RD CS R DOC REDSTONE ARSENAL AL 35898-5241	1
ARMY MISSILE CMND AMSMI REDSTONE ARSENAL AL 35898-5253	1
ARMY INTEL CTR AND FT HUACHUCA ATSI CDC C FT HUACHUCA AZ 85613-7000	1
NORTHROP CORPORATION ELECTR SYST DIV ATTN MRS T BROHAUGH 2301 W 120TH ST BOX 5032 HAWTHORNE CA 90251-5032	1
NAVAL WEAPONS CTR CODE 3331 ATTN DR SHLANTA CHINA LAKE CA 93555	1
PACIFIC MISSILE TEST CTR GEOPHYSICS DIV ATTN CODE 3250 POINT MUGU CA 93042-5000	1
LOCKHEED MIS & SPACE CO ATTN KENNETH R HARDY ORG 91 01 B 255 3251 HANOVER STREET PALO ALTO CA 94304-1191	1

NAVAL OCEAN SYST CTR CODE 54 ATTN DR RICHTER SAN DIEGO CA 92152-5000	1
METEOROLOGIST IN CHARGE KWAJALEIN MISSILE RANGE PO BOX 67 APO SAN FRANCISCO CA 96555	1
DEPT OF COMMERCE CTR MOUNTAIN ADMINISTRATION SPRRT CTR LIBRARY R 51 325 S BROADWAY BOULDER CO 80303	1
DR HANS J LIEBE NTIA ITS S 3 325 S BROADWAY BOULDER CO 80303	1
NCAR LIBRARY SERIALS NATL CTR FOR ATMOS RSCH PO BOX 3000 BOULDER CO 80307-3000	1
DEPT OF COMMERCE CTR 325 S BROADWAY BOULDER CO 80303	1
DAMI POI WASH DC 20310-1067	1
MIL ASST FOR ENV SCI OFC OF THE UNDERSEC OF DEFNS FOR RSCH & ENGR R&AT E LS PENTAGON ROOM 3D129 WASH DC 20301-3080	1
DEAN RMD ATTN DR GOMEZ WASH DC 20314	1

SPACE NAVAL WARFARE SYST CMND PMW 145 1G WASH DC 20362-5100	1
ARMY INFANTRY ATSH CD CS OR ATTN DR E DUTOIT FT BENNING GA 30905-5090	1
AIR WEATHER SERVICE TECH LIBRARY FL4414 3 SCOTT AFB IL 62225-5458	1
USAFETAC DNE ATTN MR GLAUBER SCOTT AFB IL 62225-5008	1
HQ AWS DOO 1 SCOTT AFB IL 62225-5008	1
ARMY SPACE INSTITUTE ATTN ATZI SI 3 FT LEAVENWORTH KS 66027-5300	1
PHILLIPS LABORATORY PL LYP ATTN MR CHISHOLM HANSCOM AFB MA 01731-5000	1
ATMOSPHERIC SCI DIV GEOPHYSICS DIRCTRT PHILLIPS LABORATORY HANSCOM AFB MA 01731-5000	1
PHILLIPS LABORATORY PL LYP 3 HANSCOM AFB MA 01731-5000	1
RAYTHEON COMPANY ATTN DR SONNENSCHN 528 BOSTON POST ROAD SUDBURY MA 01776 MAIL STOP 1K9	1

ARMY MATERIEL SYST ANALYSIS ACTIVITY AMXSY ATTN MP H COHEN APG MD 21005-5071	1
ARMY MATERIEL SYST ANALYSIS ACTIVITY AMXSY AT ATTN MR CAMPBELL APG MD 21005-5071	1
ARMY MATERIEL SYST ANALYSIS ACTIVITY AMXSY CR ATTN MR MARCHET APG MD 21005-5071	1
ARL CHEMICAL BIOLOGY NUC EFFECTS DIV AMSRL SL CO APG MD 21010-5423	1
ARMY MATERIEL SYST ANALYSIS ACTIVITY AMXSY APG MD 21005-5071	1
NAVAL RESEARCH LABORATORY CODE 4110 ATTN MR RUHNKE WASH DC 20375-5000	1
ARMY MATERIEL SYST ANALYSIS ACTIVITY AMXSY CS ATTN MR BRADLEY APG MD 21005-5071	1
ARMY RESEARCH LABORATORY AMSRL D 2800 POWDER MILL ROAD ADELPHI MD 20783-1145	1

ARMY RESEARCH LABORATORY AMSRL OP SD TP TECHNICAL PUBLISHING 2800 POWDER MILL ROAD ADELPHI MD 20783-1145	1
ARMY RESEARCH LABORATORY AMSRL OP CI SD TL 2800 POWDER MILL ROAD ADELPHI MD 20783-1145	1
ARMY RESEARCH LABORATORY AMSRL SS SH ATTN DR SZTANKAY 2800 POWDER MILL ROAD ADELPHI MD 20783-1145	1
ARMY RESEARCH LABORATORY AMSRL 2800 POWDER MILL ROAD ADELPHI MD 20783-1145	1
NATIONAL SECURITY AGCY W21 ATTN DR LONGBOTHUM 9800 SAVAGE ROAD FT GEORGE G MEADE MD 20755-6000	1
ARMY AVIATION CTR ATZQ D MA ATTN MR HEATH FT RUCKER AL 36362	1
OIC NAVSWC TECH LIBRARY CODE E 232 SILVER SPRINGS MD 20903-5000	1
ARMY RSRC OFC ATTN DRXRO GS PO BOX 12211 RTP NC 27009	1
DR JERRY DAVIS NCSU PO BOX 8208 RALEIGH NC 27650-8208	1

ARMY CCREL CECRL GP ATTN DR DETSCH HANOVER NH 03755-1290	1
ARMY ARDEC SMCAR IMI I BLDG 59 DOVER NJ 07806-5000	1
ARMY SATELLITE COMM AGCY DRCPM SC 3 FT MONMOUTH NJ 07703-5303	1
ARMY COMMUNICATIONS ELECTR CTR FOR EW RSTA AMSEL EW D FT MONMOUTH NJ 07703-5303	1
ARMY COMMUNICATIONS ELECTR CTR FOR EW RSTA AMSEL EW MD FT MONMOUTH NJ 07703-5303	1
ARMY DUGWAY PROVING GRD STEDP MT DA L 3 DUGWAY UT 84022-5000	1
ARMY DUGWAY PROVING GRD STEDP MT M ATTN MR BOWERS DUGWAY UT 84022-5000	1
DEPT OF THE AIR FORCE OL A 2D WEATHER SQUAD MAC HOLLOMAN AFB NM 88330-5000	1
PL WE KIRTLAND AFB NM 87118-6008	1
USAF ROME LAB TECH CORRIDOR W STE 262 RL SUL 26 ELECTR PKWY BLD 106 GRIFFISS AFB NY 13441-4514	1

AFMC DOW WRIGHT PATTERSON AFB OH 0334-5000	1
ARMY FIELD ARTLLRY SCHOOL ATSF TSM TA FT SILL OK 73503-5600	1
NAVAL AIR DEV CTR CODE 5012 ATTN AL SALIK WARMINISTER PA 18974	1
ARMY FOREIGN SCI TECH CTR CM 220 7TH STREET NE CHARLOTTESVILLE VA 22901-5396	1
NAVAL SURFACE WEAPONS CTR CODE G63 DAHLGREN VA 22448-5000	1
ARMY OEC CSTE EFS PARK CENTER IV 4501 FORD AVE ALEXANDRIA VA 22302-1458	1
ARMY CORPS OF ENGRS ENGR TOPOGRAPHICS LAB ETL GS LB FT BELVOIR VA 22060	1
TAC DOWP LANGLEY AFB VA 23665-5524	1
ARMY TOPO ENGR CTR CETEC ZC 1 FT BELVOIR VA 22060-5546	1
LOGISTICS CTR ATCL CE FT LEE VA 23801-6000	1

SCI AND TECHNOLOGY 101 RESEARCH DRIVE HAMPTON VA 23666-1340	1
ARMY NUCLEAR CML AGCY MONA ZB BLDG 2073 SPRINGFIELD VA 22150-3198	1
ARMY FIELD ARTLLRY SCHOOL ATSF F FD FT SILL OK 73503-5600	1
USATRADO ATCD FA FT MONROE VA 23651-5170	1
ARMY TRADOC ANALYSIS CTR ATRC WSS R WSMR NM 88002-5502	1
ARMY RESEARCH LABORATORY AMSRL BE M BATTLEFIELD ENVIR DIR WSMR NM 88002-5501	1
ARMY RESEARCH LABORATORY AMSRL BE A BATTLEFIELD ENVIR DIR WSMR NM 88002-5501	1
ARMY RESEARCH LABORATORY AMSRL BE W BATTLEFIELD ENVIR DIR WSMR NM 88002-5501	1
ARMY RESEARCH LABORATORY AMSRL BE ATTN MR VEAZEY BATTLEFIELD ENVIR DIR WSMR NM 88002-5501	1
DEFNS TECH INFO CTR CENTER DTIC BLS BLDG 5 CAMERON STATION ALEXANDRIA VA 22304-6145	1



ARMY MISSILE CMND AMSMI REDSTONE ARSENAL AL 35898-5243	1
ARMY DUGWAY PROVING GRD STEDP 3 DUGWAY UT 84022-5000	1
USATRADO ATCD FA FT MONROE VA 23651-5170	1
ARMY FIELD ARTLRY SCHOOL ATSF FT SILL OK 73503-5600	1
WSMR TECH LIBRARY BR STEW IM IT WSMR NM 88001	1
Record Copy	10
Total	96